



DS1387

soundmasking, paging and music speaker for 70.7 volt systems

The industry's largest supplier of design-build soundmasking solutions

tech spec_sheet

Features:

- Dual horizontally opposed speakers.
- Internal 70.7 volt transformer with rotary volume control
- Single point suspension for easy installation
- UL listed to conform to UL1480 and UL2043
- Made in USA.



Description:

The DS1387 contains dual horizontally opposed four-inch diameter speakers. The compact enclosure includes a convoluted, flame-retardant, acoustical insert to eliminate standing waves and metallic resonance. Dynasound's DS1387 soundmasking speaker is designed for quick and easy installation under raised access floors and above suspended ceilings. The DS1380 provides uniform dispersion and is well suited for soundmasking, paging and music signals.

Specifications:

Loudspeaker:	Dual four inch diameter premium loudspeaker
Transformer:	Primary 70.7v, Secondary 8 Ohms, Switch Positions: 1/4, 1/2, 1, 2, 4 watts
Dimensions:	4.5 inches x 4.5 inches x 6 inches
Weight:	6 lbs.
Finish:	black

Architect's Specification:

Soundmasking assembly shall be Dynasound model DS1380. Unit shall contain dual 4" diameter loudspeakers, equipped with a 70.7V transformer, rectangular enclosure, acoustical baffle, and suspension eye-bolt. The unit shall be factory assembled, wired and ready for installation. The unit shall include an external tap selector switch with an off position and 1/4, 1/2, 1, 2 and 4 watt power taps clearly identified. Strain relief shall be provided to protect hook-up leads. The enclosure shall measure 6 inches long x 4 inches wide x 4 inches tall. Enclosure shall be internally acoustically dampened. Speaker shall be UL listed to conform to UL1480, UL2043.

Use with:



DS1042 system



DS1092 system



DS1625 amplifier



DSRMP-Attenuator